



## Merlo Models

<b>Panoramic:</b>	Weight (lbs)	Lifting Capacity (ft)	Max. Lift Height (ft)	Max. Forward Reach (ft)	Dimensions (LWH-ft)	Top Speed (mph)
P25.6	9,900	5,500lbs	19'3"	10'8"	12'7"x5'9"x6'2"	15
P28.8L	13,300	6,200lbs	26'9"	17'3"	13'9"x6'5"x7'	15
P32.6L	13,135	7,000lbs	20'9"	11'1"	13'8"x6'5"x7'	15
P28.8L PLUS	13,300	6,200lbs	26'9"	17'3"	13'9"x6'5"x7'	25
P32.6L PLUS	13,135	7,000lbs	20'9"	11'1"	13'8"x6'5"x7'	25
P28.8PLUS	13,300	6,200lbs	26'9"	17'3"	13'9"x6'5"x7'	25
P32.6PLUS	13,135	7,000lbs	20'9"	11'1"	13'8"x6'5"x7'	25
P28.8TOP	13,300	6,200lbs	26'9"	17'3"	13'9"x6'5"x7'	25
P32.6TOP	13,135	7,000lbs	20'9"	11'1"	13'8"x6'5"x7'	25
P34.7	14,500	7,500lbs	22'9"	11'8"	13'7"x7'3"x8'1"	15
P34.10	15,980	7,500lbs	31'8"	20'6"	14'2"x7'3"x8'1"	15
P36.7	14,900	8,000lbs	22'9"	11'8"	14'1"x7'3"x8'1"	15
P36.10	16,200	8,000lbs	31'8"	20'6"	14'2"x7'3"x8'1"	15
P40.9	17,100	8,800lbs	29'5"	17'	16'3"x7'2"x8'	15
P37.12PLUS	19,175	8,200lbs	37'7"	24'9"	15'9"x7'2"x8'	25
P40.9PLUS	17,100	8,800lbs	29'5"	17'	16'3"x7'2"x8'	25
P39.10 STABILIZERS	18,300	8,600lbs	34'4"	22'6"		15
P38.12 STABILIZERS	18,800	8,400lbs	38'	24'9"	15'9"x7'2"x8'	15
P38.13 STABILIZERS	19,000	8,400lbs	41'3"	28'2"	17'1"x7'2"x8'	15
P38.14 STABILIZERS	20,000	8,400lbs	44'6"	29'8"	18'3"x7'2"x8'	15
P38.12PLUS	18,800	8,400lbs	38'	24'9"	15'9"x7'2"x8'	25
P38.13PLUS	19,000	8,400lbs	41'3"	28'2"	17'1"x7'2"x8'	25
P38.14PLUS	20,000	8,400lbs	44'6"	29'8"	18'3"x7'2"x8'	25
P40.16 STABILIZERS	22,600	8,800lbs	51'1"	37'4"	18'2"x7'8"x8'2"	25
P40.17 STABILIZERS	22,800	8,800lbs	54'7"	41'	19'x7'8"x8'2"	25
P55.9CS	22,745	12,100lbs	28'2"	15'	16'7"x7'8"x8'1"	25
P60.9CS	24,100	13,200lbs	28'2"	15'	16'7"x7'8"x8'1"	25
P75.9CS	25,125	16,500lbs	28'2"	15'	16'7"x7'8"x8'1"	25
P60.10	22,000	13,200lbs	31'3"	18'	17'5"x7'3"x8'	25
P72.10	23,000	16,000lbs	31'3"	18'	17'5"x7'3"x8'	25
P50.18 HM		11,000lbs	58'5"	45'9"		25
P65.14 HM	34,100	14,300lbs	45'6"	29'5"	19'4"x7'9"x9'4"	25
P101.10 HM (brochure)	33,500	22,000lbs	32'	18'7"	18'8"x7'9"x9'4"	25
P120.10HM	34,500	26,500lbs	32'	18'10"	18'10"x7'10"x9'4"	25

<b>Roto:</b>	Weight (lbs)	Max. Load Capacity (lbs)	Max. Lift Height (ft)	Max. Forward Reach (ft)	Top Speed (mph)
38.14		8,400	45'6"	36'	15
38.16		8,400	51'5"	42'6"	15
50.10 S	25,963	11,000	34'1"	25'	25
38.14 S	26,271	8,400	45'6"	36'	25
38.16 S	26,624	8,400	51'5"	42'6"	25
45.19	32,398	10,000	61	51'8"	16
45.21	32,839	10,000	68	59'	16
50.16 MCSS	31,296	11,000	53'8"	44'	25
45.19 MCSS	31,517	10,000	61'3"	52'2"	25
45.21 MCSS	31,958	10,000	68'2"	59'	25
40.25 MCSS	34,051	8,800	82'8"	74'4"	25
40.26 MCSS	34,051	8,800	85'3"	75'1"	25
40.30 MCSS	42,328	8,818	95'8"	83'6"	25
45.21 MCTJ	33,941	10,000	104'	41'6"	25
60.24 MCSS	41,336	13,228	78.7"	66'6"	25